

SA25

The arm shall be SA25-\_\_\_\_\_ (specify configuration) arm, consisting of a bent arm welded onto a pole adaptor. Multiple arms shall be welded to an aluminum pole adaptor with cast aluminum horizontal bars.

The arm shall be made of 2-3/8" OD, 0.154" thick aluminum extrusion welded onto cast aluminum pole adaptor. An optional scroll shall be made of 1-1/2"W x 1/4" thick aluminum flat bar. All hardware shall be tamper resistant, stainless steel.

A variety of configurations is available, some of which are illustrated below. Those not illustrated are noted in the bottom left-hand corner. Non-standard configurations may be feasible, please consult factory for details.



Arms shall feature pole adaptor with a decorative cast aluminum cover. A 2" ID opening is provided on the fixture side. Arms are not pre-wired and shall be wired by the contractor.

## SA25

Arm	Layout	Color
-----	--------	-------

- W** - wall bracket
- A** - single at 90°
- A-SCR** - single at 90° with scroll
- B** - twin at 180°
- C** - triple at 90°
- D** - quad at 90°
- BLK** - black
- GRN** - green
- BRZ** - bronze
- GRY** - grey
- WHT** - white
- CTM** - custom

### ADDITIONAL CONFIGURATIONS AVAILABLE



### Suggested pole and luminaire combinations

