
SH50



Specifications

The SH50 series square luminaire shall consist of a roof assembly. cage, diffuser, capital, ballast assembly and an internal optical system. The hinged roof shall be made of cast aluminum and shall have a spun aluminum cupola and a cast aluminum finial. The diffuser shall be either clear, frosted or white acrylic or polycarbonate or clear tempered glass. The cage shall be made of cast aluminum and shall be welded to the capital. All castings shall be formed true to pattern, with no warping or mold shifting.

The electrical and optical components shall be mounted on a cast aluminum ballast plate within the capital. The medium or mogul porcelain socket shall be 4kV pulse rated. The HID ballast shall be HPF, CWA, multi-tap, supplied with capacitor and ignitor. Luminaire shall be ETL certified as suitable for wet locations. Lamps by others.

LEDs shall be Cree X-Lamp XP-L White, with sealed LediL Strada optics. Class II driver shall be 50,000+ hours rated.

The optical assembly shall be mechanically secured to the ballast plate and/or the roof, as appropriate.

The luminaire shall mount to a 3"OD or 4"OD x 3"H tenon with three sets of two stainless steel tamper resistant screws. All exposed metal parts shall receive baked-on smooth semi-gloss powder coat finish. Ships boxed and palletized.





CA clear acrylic FA frosted acrylic **CP** clear polycarbonate **FP** frosted polycarbonate WP sign white polycarbonate TG tempered glass



5M 50MH **7M** 70MH 10M 100MH 15M 150MH 25M 250MH

5H 50HPS **7H** 70HPS **10H** 100HPS 15H 150HPS

25H 250HPS

5L4K 50W LED 4000K, 5660 lm **8L4K** 82W LED 4000K, 9287 lm



1 120V 2 208V 3 240V 4 277V 5 347V

6 480V U 120-277V

CO - dual optical cone IES V HR3 - rooftop reflector, horizontal lamp, IES III LV - louver

stack IES V II IES II (LED) IV IES IV (LED) VIES V(LED)

SP01

T 1-866-667-9517



BA - bare lamp

R5 - glass refractor IES V

R3 - glass refractor IES III

FA finial "A"



HS - house side shield

SF - single fuse DF - double fuse **BP** - button photocell

LP - locking photocell GC - glass

chimney FN - no finial



Sheridan lighting systems, inc.



Sheridan Lighting Systems, Inc.

E sales@sheridansys.com

SA01-A

BLK

Color

BLK black

BRZ bronze

GRN green

GRY grey

WHT white

CTM custom