



EPA: 1.89

Weight: approx. 22 lbs

The SH65 series luminaire shall consist of an opal white domed acrylic diffuser, extruded aluminum body with decorative grooves, a cast aluminum slip fitter, an internal ballast assembly, an internal optical system and a lower diffuser assembly. The hinged lower diffuser assembly shall be secured to the luminaire with stainless steel hardware. All castings shall be formed true to pattern, with no warping or mold shifting.

The electrical and optical components shall be mounted within the luminaire. The medium or mogul porcelain socket shall be 4kV pulse rated. The HID ballast shall be HPF, CWA, multi-tap, supplied with capacitor and ignitor. Luminaire shall be ETL certified as suitable for wet locations. Lamps by others.

The luminaire shall feature optional uplight component via an opening between the reflector and the domed diffuser (see "Options" below for catalog designation).

The luminaire shall mount to a 2" pipe (2.38"OD) tenon with stainless steel bolts. All exposed metal parts shall receive baked-on smooth semi-gloss powder coat finish. Ships boxed and palletized.

SH65

Luminaire	Diffuser	Ballast	Voltage
	<p>CP clear polycarbonate</p> <p>CG clear tempered glass</p>	<p>5M - 50MH</p> <p>7M - 70MH</p> <p>10M - 100MH</p> <p>15M - 150MH</p> <p>17M - 175MH</p> <p>25M - 250MH</p>	<p>1 - 120V</p> <p>2 - 208V</p> <p>3 - 240V</p> <p>4 - 277V</p> <p>5 - 347V</p>
		<p>5H - 50HPS</p> <p>7H - 70HPS</p> <p>10H - 100HPS</p> <p>15H - 150HPS</p> <p>25H - 250HPS</p>	

HR3

Optics	Options	Color
HR3 - aluminum reflector, horizontal lamp, IES III	<p>HS - house side shield</p> <p>SF - single fuse</p> <p>DF - double fuse</p> <p>UP - uplight component</p>	<p>BLK - black</p> <p>GRN - green</p> <p>BRZ - bronze</p> <p>GRY - grey</p> <p>WHT - white</p> <p>CTM - custom</p>

Suggested pole and bracket combinations

